




## Standard Generator

- **High Fuel Efficiency**
- **Ultimate Durability**  
100% Copper Wire for Alternator  
Anti-Rusty fuel tank  
Full roll cage for ultimate protection
- **Less Vibration & Quiet Operation**
- **All models have oil alert function.**



### Specification

Model		GV-3000	GV-7000S	GV-3200	GV-7600S
GENERATOR	Phase	Single			
	Voltage Regulation	AVR			
	Rated Output	2 kVA	5 kVA	2.3 kVA	5.5 kVA
	Maximum Output	2.2 kVA	5.5 kVA	2.5 kVA	6 kVA
	Rated Frequency	50 Hz		60 Hz	
	Rated Voltage	220 V			
	Rated Ampere	9.1A	22.7 A	10.5 A	25 A
	DC Output	12 V/8.3 A			
	Continuous Running Time (rated load)	9.5 h	7.5 h	6.3 h	5 h
	Tank Capacity	12.6 L	22.6 L	12.6 L	22.6 L
Receptacle					
		European socket, CEE 7/4, 2pcs	European socket, CEE 7/4, 1pc NEMA L6-30 Socket, 1pc	BS1363, 2pcs OR CEE 7/4, 2pcs	BS1363, 2pcs OR CEE 7/4 NEMA L6-30
ENGINE	Model	Koshin K210	Koshin K420	Koshin K210	Koshin K420
	Type	Air-cooled, 4-stroke, OHV, single cylinder			
	Displacement	212 cc	420 cc	212 cc	420 cc
	Oil Alert System	Standard			
	Starting system	Recoil	Recoil/Electric starter	Recoil	Recoil/Electric starter
	Battery	—	Maintenance-free type	—	Maintenance-free type
Wheel Kit	—	Standard	—	Standard	
Net Weigh	42 kg (93 lbs)	85 kg (187 lbs)	42.6 kg (94 lbs)	85 kg (187 lbs)	
Gross Weigh	44 kg (97 lbs)	87 kg (192 lbs)	45 kg (99 lbs)	89 kg (196 lbs)	
Dimensions L×W×H (mm)	615 × 445 × 457	695 × 534 × 547	615 × 445 × 457	695 × 534 × 547	
Packing Unit	1				

\*GV-7000S/GV-7600S without battery